

SPRAY SUPPRESSION MUDFLAPS



- Lightweight – weighs only 5.75 kgs per square metre.
- Easy to fit – fits snugly into mudguards without cutting, no side channels.
- Anti-sail – excellent anti-sail properties.
- Market Leading Brand.
- Approved – Clear Pass conforms to all existing legislation for energy absorbing mudflaps BS AU 200/2A, 91/226/EEC, 2010/19/EU.
- Other sizes available on request.
- Homologation No. A e6 2020.



SPRAY SUPPRESSION MUDFLAPS – UK SPECIFICATION

PART NO.	WIDTH (W)	LENGTH (L)	SUITS MUDGUARD
CPF15	400mm (15¾")	560mm (22")	IT420T, IT420S, IT420X
CPF16	410mm (16")	560mm (22")	IT450
CPF17	430mm (17")	560mm (22")	IT450
CPF18	460mm (18")	560mm (22")	IT480, IT500T, IT500
CPF20	510mm (20")	560mm (22")	IT530, IT530LP
CPF22	560mm (22")	560mm (22")	IT570
CPF23	585mm (23")	560mm (22")	IT610, IT615
CPF24	610mm (24")	560mm (22")	IT650, IT650LP
CPF25	635mm (25")	560mm (22")	IT670
CPF26	660mm (26")	560mm (22")	IT690, IT695, IT710
CPF2624	660mm (26")	610mm (24")	IT690, IT695, IT710
CPF28	710mm (28")	560mm (22")	UNIVERSAL

SPRAY SUPPRESSION MUDFLAPS – EUROPEAN SPECIFICATION

PART NO.	WIDTH (W)	LENGTH (L)	SUITS MUDGUARD
ECPF15	400mm (15¾")	750mm (29½")	IT420T, IT420S, IT420X
ECPF16	410mm (16")	750mm (29½")	IT450
ECPF17	430mm (17")	750mm (29½")	IT450
ECPF18	460mm (18")	750mm (29½")	IT480, IT500T, IT500
ECPF20	510mm (20")	750mm (29½")	IT530, IT530LP
ECPF22	560mm (22")	750mm (29½")	IT570
ECPF23	585mm (23")	750mm (29½")	IT610, IT615
ECPF24	610mm (24")	750mm (29½")	IT650, IT650LP
ECPF25	635mm (25")	750mm (29½")	IT670
ECPF26	660mm (26")	750mm (29½")	IT690, IT695, IT710

All dimensions nominal.

The manufacturer reserves the right to alter sizes, specifications etc. without prior notice