



Spray Supression Mudflaps

Product Information

- Lightweight – weighs only 5.75 kgs per square metre
- Easy to fit – fits snugly into mudguards without cutting, no side channels
- Anti-sail – excellent anti-sail properties
- Complies with European Directive (EU)109/2011
- Non-standard sizes on request
- Homologation No. A e6 0025

IMPORTANT When cutting/trimming Clear Pass flaps, **DO NOT** remove the e-mark stamping. Doing so will invalidate all legal and type approval requirements.



Spray Supression Mudflaps UK Specification

Part No.	Width (W)	Length (L)	Suits Mudguard
CPF15	400mm (15¾")	560mm (22")	IT420T, IT420S, IT420X
CPF16	410mm (16")	560mm (22")	IT450
CPF17	430mm (17")	560mm (22")	IT450
CPF18	460mm (18")	560mm (22")	IT480, IT500T, IT500
CPF20	510mm (20")	560mm (22")	IT530, IT530LP
CPF22	560mm (22")	560mm (22")	IT570
CPF23	585mm (23")	560mm (22")	IT610, IT615
CPF24	610mm (24")	560mm (22")	IT650, IT650LP
CPF2424	610mm (24")	610mm (24")	IT650, IT650LP
CPF25	635mm (25")	560mm (22")	IT670
CPF26	660mm (26")	560mm (22")	IT690, IT695, IT710
CPF2624	660mm (26")	610mm (24")	IT690, IT695, IT710
CPF27	685mm (27")	560mm (22")	IT710
CPF28	710mm (28")	560mm (22")	UNIVERSAL

Spray Supression Mudflaps European Specification

Part No.	Width (W)	Length (L)	Suits Mudguard
ECPF15	400mm (15¾")	710mm (28")	IT420T, IT420S, IT420X
ECPF16	410mm (16")	710mm (28")	IT450
ECPF17	430mm (17")	710mm (28")	IT450
ECPF18	460mm (18")	710mm (28")	IT480, IT500T, IT500
ECPF20	510mm (20")	710mm (28")	IT530, IT530LP
ECPF22	560mm (22")	710mm (28")	IT570
ECPF23	585mm (23")	710mm (28")	IT610, IT615
ECPF24	610mm (24")	710mm (28")	IT650, IT650LP
ECPF25	635mm (25")	710mm (28")	IT670
ECPF26	660mm (26")	710mm (28")	IT690, IT695, IT710
ECPF27	685mm (27")	710mm (28")	IT710
ECPF28	710mm (28")	710mm (28")	UNIVERSAL

EC Whole Vehicle Type Approval

With the advent of EC Whole Vehicle Type Approval, 2007/46/EC introduced in 2007 and certain amendments made latterly. It is now a mandatory requirement on vehicle categories N₂ (vehicles over 7.5 tonnes) N₃, O₃ and O₄, to adopt the European Fitment Criteria, which can only be achieved in most cases with Spray Supressions mudflaps of 710mm and over in length. UK specification Spray Supression mudflaps are permissible for retrofit on vehicles registered prior to EC Whole Vehicle Type Approval.